

ISO Property

| starex° | Grade | VI-6120N |
|---------|------------|------------------------------------|
| | Resin Type | Halogen Free Flame Retardant PP/MF |

| Item | Measuring Method | Condition | Unit | Value | | | |
|-----------------------------|------------------|------------------|-------------------|---------|--|--|--|
| Physical | | | | | | | |
| Specific Gravity | ISO 1183 | Natural color | g/cm3 | 1.2 | | | |
| MVR | ISO 1133 | 230°C, 2.16kg | g/10min | 10 | | | |
| Mold Shrinkage-MD | ISO 294-4 | 23°C | % | 0.8~1.1 | | | |
| Mold Shrinkage-TD | ISO 294-4 | 23°C | % | 0.9~1.2 | | | |
| Mechanical | | | | | | | |
| Tensile Strength at Yield | ISO 527 | 50mm/min | MPa | 21 | | | |
| Flexural Strength | ISO 178 | 2mm/min | MPa | 30 | | | |
| Flexural Modulus | ISO 178 | 2mm/min | МРа | 2,600 | | | |
| Charpy Impact (notched) | ISO 179 1eA | at 23°C, 4mm | KJ/m ² | 3 | | | |
| Thermal CLE A CA | | | | | | | |
| Heat Deflection Temperature | ISO 75-2 | 0.45MPa, 120°C/h | °C | 110 | | | |
| Flame Class | | | | | | | |
| Flame Class | UL94 | V0 | mm | 1.5 | | | |
| Flame Class | UL94 | 5VA | mm | 1.5 | | | |

- 1. The value above is the representative value of the NP or representative color and may have deviation. It can only be used for selecting materials.
- 2. The value above shall not be regarded as a material specification and cannot be used for molding designs.

Information inserted in this document such as data, statements, representative values, etc. are provided solely for customer convenience. It does not expressly or impliedly guarantee anything regarding the safety or practicability of the (1) materials, (2) products, and/or (3) design that utilizes recommendations or proposals, of LOTTE CHEMICAL. Furthermore, nothing in the contents of this document shall have any legal binding effect, and especially, the representative value is simply for reference and is not a minimum value that has legal binding effect. Whether materials and/or products of LOTTE CHEMICAL and/or a design that uses or utilizes LOTTE CHEMICAL's recommendations or proposals are (is) compatible with individual uses shall be determined solely by each user and such user shall be solely responsible for any results, including but not limited to, any and all loss and damages incurred due to such uses. Users must implement and verify all testing and analyses for proving the safety and compatibility of final products that have been created or altered by using LOTTE CHEMICAL's materials or products. The data and values inserted and/or contained in this document may be changed due to quality improvement of the product without any prior notification.

★ The last update date : 21/05/2021